

DEVELOPERS AND REPLENISHERS FOR THERMAL PLATES

DIRECT USE DEVELOPER FOR THERMAL POSITIVE PLATES.

PROPERTIES

- ▶ Minimum aggression towards coating in the image areas obtaining the maximum cleaning of the non images areas.
- ▶ Auto-replenisher. The multipurpose property of **DEVELOPER IP-T8** permits its use as both developer and replenisher, maintaining in the bath the correct conductivity values.
- ▶ High emulsion dissolving properties to minimize the accumulation of residues in the automatic processor.
- ▶ Long life in processor.

APPLICATION

- ▶ Development in processors for thermal plates.
- ▶ Direct use.

METHOD OF USE

- ▶ Recommended working temperature: 23 °C ± 1 °C.
- ▶ Development time: 30 ± 5 seconds in immersion.
- ▶ Replenishment: Use **DEVELOPER IP-T8** as a replenisher.
- ▶ Replenishment rate: 120 ml/m².
- ▶ Antioxidant Stand by ON: 100 ml/h.
- ▶ Antioxidant Stand by OFF: 100 ml/h.

CONSIDERATIONS

- ▶ Adequate replenishment keeps filters and circulation systems clean prolonging the life of the bath.
- ▶ Correct cleaning of the equipment will avoid contamination of the new bath and prolong the life of the processor. Clean using **PROCESSOR CLEANER PC-520** and **PROCESSOR CLEANER PC-600**.

PACKAGING

- ▶ 20, 200 and 1.000 liters.

Note:
The results obtained may vary depending if the conditions of use are outside of our recommended values.