

DEVELOPERS AND REPLENISHERS FOR CTcP PLATES

DIRECT USE DEVELOPER FOR CTcP POSITIVE PLATES.

PROPERTIES

- ▶ Minimum aggression towards coating in the image areas obtaining the maximum cleaning of the non images areas.
- ▶ High emulsion dissolving properties to minimize the accumulation of residues in the automatic processor.
- ▶ Long life in processor.

APPLICATION

- ▶ Development in processors for CTcP positive plates.
- ▶ Direct use.

METHOD OF USE

- ▶ Recommended working temperature: 23 °C ± 1 °C.
- ▶ Development time: 25 ± 5 seconds in immersion.
- ▶ Replenishment: Use **DEVELOPER IP-C01** or **REPLENISHER R-C01**.
- ▶ Replenishment rate: 120 ml/m². 50 ml/m².
- ▶ Antioxidant Stand by ON: 100 ml/h. 40 ml/h.
- ▶ Antioxidant Stand by OFF: 100 ml/h. 40 ml/h.

CONSIDERATIONS

- ▶ Adequate replenishment keeps filters and circulation systems cleaned prolonging the life of the bath.
- ▶ Correct cleaning of the equipment will avoid contamination of the new bath and prolong the life of the processor.
Clean using **PROCESSOR CLEANER PC-520** and **PROCESSOR CLEANER PC-600**.

PACKAGING

- ▶ 20 liters.
- ▶ Other packaging available on request.

Note:
The results obtained may vary depending if the conditions of use are outside of our recommended values.