

DEVELOPERS AND REPLENISHERS FOR ANALOGUE PLATES

DIRECT USE DEVELOPER FOR POSITIVE PLATES.

PROPERTIES

- ▶ Buffered. Reduces the negative effects caused by poor contact between film and plate.
- ▶ Auto-replenisher. The multipurpose property of **DEVELOPER HF-LD** permits its use as both developer and replenisher maintaining in the bath the correct conductivity values.
- ▶ Long life in processor.

APPLICATION

- ▶ Applicable for all positive plate lines, it is recommended for:
 - ▶ Hand development.
 - ▶ Development in processors with immersion and spray systems.
 - ▶ Tray or dish development.

METHOD OF USE

- ▶ Recommended working temperature:
 - ▶ Hand: 20 - 22°C
 - ▶ Processor: 24 °C ± 1 °C
- ▶ Development time:
 - ▶ Hand: 45 - 60 seconds
 - ▶ Processor: 30 ± 5 segundos
- ▶ Replenishment rate: 100 - 120 ml/m²

CONSIDERATIONS

- ▶ Adequate replenishment keeps filters and circulation systems clean prolonging the life of the bath.
- ▶ Correct cleaning of the equipment will avoid contamination of the new bath and prolong the life of the processor.
- ▶ Clean using **PROCESSOR CLEANER PC-520** and **PROCESSOR CLEANER PC-600**.

PACKAGING

- ▶ 10 litres.
- ▶ 20 litres.
- ▶ 200 litres (with dosing device).

Note:
The results obtained may vary depending if the conditions of use are outside of our recommended values.